

6210AB-C

SOFT SERVE FREEZER

1 Flavor, Countertop, Pump, Pasteurization







Most Compact & Versatile single flavor counter model with Auto-Pasteurization with intelligent control

Auto-Pasteurization

Significantly reduces frequency of cleaning to every 21 days with scheduled daily auto-pasteurization

Digital Control and Display

Microprocessor control provides access to system settings and additional functions. Digital interface displays critial info as system status, temperatures, dispense count, errors, etc.

Operation Logging

Logs every operation and error to provide history and data for easy troubleshooting

Auto Programming

Allows automatic switching of operation modes based on preset scheduels $% \left(1\right) =\left(1\right) +\left(1\right) +\left($

Ideal for any restaurants, convenience stores, dessert stands and delis to serve ice cream and gelato but with desire for significant reduction in labor cost of cleaning.

Hopper Agitators

Maintain product consistency and prevent product separation

Defrost for Cleaning

Increases efficiency during cleaning by heating frozen product in cylinder

Direct Drive Transmission

Eliminates consumable moving parts and increases transmission efficiency

Safety Protections

- Low temperature and motor overload shutoffs to protect in the event of cylinder freeze up
- · High pressure switch to prevent compressor overheating

Quick Refreeze

Turn on freeze immediately to freeze down to serving viscosity when quick service is required after long idle period

Self Closing Valve with Speed Control


Automatically prevents product overflow after dispense; Provides flexibility in dispense rate control






6210AB-C

SOFT SERVE FREEZER





SPECIFICATIONS

Flavors	1
Freezing Cylinders	1 x 1.2L / 1.3qt
Mix Hoppers	1 x 8.0 L / 8.5 q t
Output Capacity (80 grams)	200 serves/hr
Clearance Requirements	150mm/6″ on back

Weight	Kg/lb
Net	118 / 262
Shipping	129 / 287
Volume	0.31 CBM / 10.84 CBF

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	384 / 15.1	450 / 17.7
Depth	777 / 30.6	800 / 31.5
Height	703 / 27.7	860/33.6

Electrical	MFS	MCA	Power(kW)
220-240/50/1	15	10	1.8
208-230/60/1	15	9	1.8

 $\boldsymbol{\cdot}$ Above specifications are subject to change without notice

FEATURES	
Control Systems	Sinqle, Digital
Refrigerated Hoppers	
Hopper Agitator	\checkmark
Temperature Display	
Standby Mode	\checkmark
Auto Clsoing Dispensing Valves	lacksquare
Dispensing Speed Control	lacksquare
Low Mix Indicator Light	
Low Mix Indicator Alarm	
Low Temperature Protection	
High Pressure Protection	\checkmark
Defrost & Refresh	
Soft Start	\checkmark
Direct Drive Pump	
Auto-Pasteurization	$\overline{\mathbf{v}}$

AVAILABLE OPTIONS	
Water Cooled	\checkmark
Top Air Discharge Chute	
Cart (Trolley)	